



**Plas-Tanks Industries, Inc.**  
 4400 Port Union Road · Fairfield, Ohio 45014  
 513-874-5047 · plastanks.com

QUOTATION

# Q-2026-5569 · Rev B

<b>DATE OF ISSUE</b>	<b>INQUIRY NO.</b>	<b>EST. COMPLETION</b>
4/23/2026	—	10–12 weeks from order release
<b>TERMS</b>	<b>F.O.B.</b>	<b>QUOTATION NO.</b>
Net 30 days, upon approved credit	F.O.B. Fairfield, Ohio	Q-2026-5569

**PREPARED FOR**

**Patrick Consulting, LLC**  
 755 Brough Ave  
 Hamilton, OH 45015  
 United States

Sam Patrick  
 splpatrick57@me.com  
 +1-513-490-1019

**SALES ENGINEER**

**Demo Admin**  
 dev@frp-tank-quoter.local  
 513-874-5047

**SCOPE OF SUPPLY**

The vessel is a vertical, cylindrical frp vessel fabricated by the filament-wound method in accordance with ASTM D-3299-18. Primary dimensions: 10'-0" ID x 12'-0" straight-shell height, with a conical drain bottom and f and d. Net shell capacity is approximately 7,050 gal.

100-mil nominal corrosion barrier: C-veil surface mat backed by two plies of chopped strand mat, wet-out with corrosion-grade resin. Structural laminate sized for the service conditions below; exterior finished with a UV-resistant pigmented topcoat.

**VESSEL**

<b>ORIENTATION</b>	<b>ID x HEIGHT</b>	<b>CAPACITY</b>
Vertical	10'-0" x 12'-0"	7,050 gal
<b>BOTTOM</b>	<b>TOP HEAD</b>	<b>RESIN SYSTEM</b>
Conical Drain	F AND D	Derakane 8084 (Elastomer-Modified)

**DESIGN CONDITIONS**



**Plas-Tanks Industries, Inc.**  
4400 Port Union Road · Fairfield, Ohio 45014  
513-874-5047 · plastanks.com

QUOTATION

# Q-2026-5569 · Rev B

SERVICE	SPECIFIC GRAVITY	OPERATING TEMP
NaOH	1.8	80°F
DESIGN TEMP	PRESSURE	VACUUM
120°F	0 psig	0 psig

Outdoor installation · Wind: 115 mph · Seismic: Ss 0.21 / S1 0.087 / Site Class D

## ACCESSORIES INCLUDED

- 1 × outlet
- 1 × inlet
- 1 × manway
- Stainless steel support stand

## INVESTMENT

Vessel — materials, fabrication & quality plan	\$47,447
Freight allowance (F.O.B. Fairfield)	\$1,600
<b>Total delivered</b>	<b>\$49,047</b>

## CLARIFICATIONS & NOTES

- Fabrication per ASTM D-3299-18 using Derakane 8084 (Elastomer-Modified) resin as the corrosion barrier.
- Post-cure per resin manufacturer recommendation prior to shipment.
- Non-code construction; certificate of conformance provided with shipment.
- Pricing is valid for 30 days. Lead time is quoted from order release and approved drawings.

ACCEPTED FOR PLAS-TANKS INDUSTRIES, INC.

ACCEPTED FOR PATRICK CONSULTING, LLC



**Plas-Tanks Industries, Inc.**  
4400 Port Union Road · Fairfield, Ohio 45014  
513-874-5047 · plastanks.com

QUOTATION

**Q-2026-5569 · Rev B**

---

DEMO ADMIN · SALES ENGINEER

AUTHORIZED SIGNATURE & DATE